

Super 10



Sistem IrriStand

Aspersor cu aplicatii multiple,
montat pe sistem IrriStand 52

Aplicatii: culturi in camp, sere, amenajari
peisagistice si rezidentiale
Destinat aplicatiilor multiple, utilizabil pe distante de
pana la 12 m

Caracteristici:

- compact, robust, mecanism cu bila, protejat ermetic
- dulie de duza pentru o utilizare facila
- optional prevazut cu regulator de presiune (RP)
- distributie ampla a apei

**Tabel de functionare in functie de media precipitatilor (mm/h)
si coeficientul de uniformitate (CU) pe distante diferite**

Culoare duza	P (bar)	Q (l/h)	D (m)	Debite (mm/hr) Distanta (m)					
				9x9	9x10	10x10	9x12	10x12	12x12
Albastra	2.5	360	18	4.5	4.0	3.6			
	3.0	395	17.5	4.9	4.4	3.9			
	3.5	425	17	5.3	4.8	4.3			
	4.0	455	17	5.6	5.1	4.6			
R.P.	3.0-5.0	360	18	4.5	4.1	3.7			
Galbena	2.5	450	20	5.7	5.1	4.6	4.3	3.8	3.2
	3.0	495	20	6.1	5.5	4.9	4.6	4.1	3.4
	3.5	530	20	6.6	5.9	5.3	4.9	4.4	3.7
	4.0	570	20	7.1	6.4	5.7	5.3	4.8	4.0
R.P.	3.0-5.0	450	20	5.5	5.0	4.5	4.2	3.7	3.1
Verde	2.5	550	20	6.7	6.0	5.4	5.0	4.5	3.8
	3.0	600	20	7.4	6.7	6.0	5.5	5.0	4.2
	3.5	650	20	8.0	7.2	6.5	6.0	5.4	4.5
	4.0	695	20	8.6	7.8	7.0	6.5	5.8	4.8
R.P.	3.0-5.0	550	20	6.9	6.2	5.6	5.2	4.3	3.9
Rosie	2.5	670	21	8.3	7.4	6.7	6.2	5.6	4.6
	3.0	735	21	9.0	8.1	7.3	6.8	6.1	5.1
	3.5	790	21	9.6	8.7	7.8	7.2	6.5	5.4
	4.0	850	21	10.5	9.4	8.5	7.9	7.1	5.9
R.P.	3.0-5.0	670	21	8.3	7.5	6.7	6.2	5.6	4.7

Cod culoare - uniformitate	CU < 85%	CU 85-88%	CU 88-92%	CU > 92%
----------------------------	----------	-----------	-----------	----------



